



## INDUSTRIAL IMAGING CLAMP METERS

# FLIR CM174/275™

The FLIR CM174 and CM275 clamp meters combine thermal imaging with electrical measurement into powerful inspection, troubleshooting, and diagnostic tools. Through Infrared Guided Measurement (IGM™), they provide a fast, reliable way to identify hot spots and overloaded circuits from a safe distance. Confirm your findings with the clamp meters' wide range of functions plus temperature readings. The FLIR CM275 also provides wireless connectivity for direct connection to the FLIR InSite™ professional workflow management app. Whether you choose the FLIR CM174 or CM275 clamp meter, inspecting and servicing plant equipment and facilities will become safer and more efficient.

[www.flir.com/IGM-Clamps](http://www.flir.com/IGM-Clamps)



### TROUBLESHOOT FASTER & SAFER

Identify electrical issues quickly with the power of IGM

- Scan entire targets for electrical issues with up to 160 x 120 thermal resolution
- Safely check for live connections using non-contact temperature measurement
- Pinpoint exact hot spot locations with laser or crosshairs
- Easily reach difficult, dark locations thanks to narrow jaw and built-in worklights



### DIAGNOSE EFFICIENTLY

Quickly verify problems, check loads, and validate hot spots

- Diagnose complex systems with high and low voltage measurement capabilities
- Use advanced electrical features including VFD mode, True RMS, and LoZ
- Expand measurement capabilities to 3000 A AC with FLIR Flex Clamp accessories
- Rely on the protection of CAT IV-600V, CAT III-1000V safety ratings



### DOCUMENT & SHARE RESULTS

Store data or share wirelessly for improved workflow

- Store electrical measurements and thermal images internally, for later review\*
- Wirelessly connect to FLIR Tools or FLIR InSite workflow management application for streamlined documentation and sharing\*

\* FLIR CM275 model only.

## SPECIFICATIONS

Thermal Imaging	CM174	CM275
IR Resolution	80 x 60 (4,800 pixels)	160 x 120 (19,200 pixels)
Thermal Imaging Detector	FLIR Lepton® microbolometer	FLIR Lepton® microbolometer
Temperature Sensitivity	150 mK	150 mK
Emissivity Settings	4 Presets with custom adjustment	4 Presets with custom adjustment
Temperature Accuracy	3°C or 3%	3°C or 3%
Temperature Range	-13°F to 302°F (-25°C to 150°C)	14°F to 302°F (-10°C to 150°C)
Field of View	50.0° x 38.6°	50.0° x 38°
Laser Pointer	Yes	Yes
Focus	Fixed	Fixed
Thermal Imaging Palette	Iron, Rainbow, Grayscale	Iron, Rainbow, Grayscale
Measurements-Both Models		
True RMS	Yes	
Auto-ranging	Yes, with manual range option	
	Range	Basic Accuracy
AC / DC Volts	1000 V	±1.0%
VFD AC Volts	1000 V	±1.0%
AC / DC LoZ V	1000 V	±1.0%
AC / DC Amps	600.0 A	±2.0%
VFD AC Amps	600.0 A	±2.0%
AC Inrush	600.0 A	±3.0%
Resistance	6.000 kΩ	±1.0%
Capacitance	1000 μF	±1.0%
Diode Test	1.5 V	±1.5%
Flex Input AC A	3000 A	±1.0%
Flex Input Frequency Counter	10.00 kHz	±0.1%

Additional Measurements	CM174	CM275
Continuity Check	600 Ω	30 Ω
Measuring Rate	3 samples per second	3 samples per second
Min/Max	Yes	Yes
General Information		
Connectivity	—	Bluetooth®
Data Logging & Storage	—	10 sets of 40K scalar measurements, 100 images
Jaw Opening	35 mm (1.38 in) 1250 MCM	35 mm (1.38 in) 1250 MCM
Auto Power Off	Yes	Yes
Worklights	Yes	Yes
Display Size	2.0 in TFT screen	2.4 in TFT screen
Battery	4 AAA batteries; optional TA04 Li-Poly rechargeable battery	3 AA batteries; optional TA04 Li-Poly rechargeable battery
Drop Test	2 m	2 m
Safety Category Rating	CAT III-1000V, CAT IV-600V	CAT III-1000V, CAT IV-600V
Size (H x W x L)	43 x 89 x 241 mm (1.7 x 3.5 x 9.5 in)	48.5 x 97 x 255 mm (1.9 x 3.8 x 10 in)
Weight	426 g (15 oz)	460 g (16 oz)
Warranty	10 year on product and detector	10 year on product and detector

Box Contents
Clamp Meter, batteries, silicone test leads, soft carrying case

Ordering Information	Order #
FLIR CM174 Imaging 600A AC/DC Clamp Meter with IGM	793950371749
FLIR CM275 Imaging Clamp Meter with Datalogging, Connectivity and IGM	793950372753

For a complete list of available accessories, go to: [flir.com/store/instruments/testaccessories](http://flir.com/store/instruments/testaccessories)

Specifications are subject to change without notice. For the most up-to-date specs, go to [www.flir.com](http://www.flir.com)

**CORPORATE HEADQUARTERS**  
FLIR Systems, Inc.  
27700 SW Parkway Ave.  
Wilsonville, OR 97070  
PH: +1 877.773.3547

**NASHUA**  
FLIR Systems, Inc.  
9 Townsend West  
Nashua, NH 03063  
USA  
PH: +1 866.477.3687

**LATIN AMERICA**  
FLIR Systems Brasil  
Av. Antonio Bardella, 320  
Sorocaba, SP 18085-852  
Brasil  
PH: +55 15 3238 7080

**CANADA**  
FLIR Systems, Ltd.  
920 Sheldon Court  
Burlington, ON L7L 5K6  
Canada  
PH: +1 800.613.0507

[www.flir.com](http://www.flir.com)  
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. 09/28/17

17-2460-INS-TAM



The World's Sixth Sense®